

# NV

## Nylon Reforçado com Fibra de Vidro

Reinforced Nylon with Fiberglass | Nylon Reforzado con Fibra de Vidrio

Dureza de Rodagem: **85 Shore "D"**

Rolling Hardness / Dureza del Rodamiento

Temperatura de Trabalho: **-40°C a + 180°C**

Work Temperature / Temperatura del Trabajo

Capacidade de Carga: **150 kg a 600 kg**

Load Capacity / Capacidad de Carga



R 62 NVY






















R 62 NVF

Roda integral de nylon reforçado com fibra de vidro. Indicada para trabalhos em fornos, estufas ou ambientes que trabalham na faixa de temperatura entre -40°C a +180°C. Oferece facilidade de movimentação, menor esforço do operador possui para manobras e baixa deformação estática.

Wheel completely made of reinforced nylon with Fiberglass. Indicated for the use in ovens, stoves and environments that operate in a temperature range from -40°C to +180°C. Offers motion facility, less effort from the operator for the maneuvers and low static deforming.

Rueda completa de nylon reforzada con fibra de vidrio. Indicada para trabajos en hornos, invernaderos y ambientes que operan en un rango de temperatura de -40°C a +180°C. Ofrece facilidad de movimiento, menos esfuerzo del operador para las maniobras y baja deformación estática.

| <br>Modelo | <br>Pol. (mm) | <br>mm | <br>mm | <br>Capacidade de Carga | <br>Mancal | <br>Pol. (mm) | <br>mm |
|---|--|---|--|--|---|--|---|
| R 312 NVF   | 3" (75)  | 30  | 38   | 150  |            | -  | 3/8"  |
| R 412 NVF   | 4" (100)   | 30  | 38   | 175  |            | -  | 1/2"  |
| R 512 NVF   | 5" (125)   | 32  | 38   | 200  |            | -  | 1/2"  |
| R 414 NVF   | 4" (100)   | 38  | 44   | 200  |            | -  | 1/2"  |
| R 514 NVF   | 5" (125)   | 38  | 44   | 300  |            | -  | 1/2"  |
| R 42 NVF  | 4" (100)   | 50  | 62   | 400  |            | -  | 5/8"  |
| R 42 NVY  | 4" (100)   | 50  | 62   | 400  |            | 1/2"   | 17 mm   |
| R 52 NVF  | 5" (125)   | 50  | 62   | 500  |            | -  | 5/8"  |
| R 52 NVY  | 5" (125)   | 50  | 62   | 500  |            | 1/2"   | 17 mm   |
| R 62 NVF  | 6" (150)   | 50  | 62   | 600  |            | -  | 5/8"  |
| R 62 NVY  | 6" (150)   | 50  | 62   | 600  |           | 1/2"   | 17 mm   |